SAFETY DATA SHEET

Date of issue/Date of revision : 22 November 2019 Version : 1.04



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

Product code : 10120DSC2396

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications, Used by spraying, Application by

non spray methods..

Use of the substance/

mixture

Coating.

1.3 Details of the supplier of the safety data sheet

PPG Coatings AC EMEA Amsterdamseweg 14 1422 AD Uithoorn Netherlands +31 (0)297 541786 Fax: +31 (0)297 541720

e-mail address of person responsible for this SDS

: PS.ACEMEA@ppg.com

National contact

PPG Coatings Denmark A/S Gladsaxevej 300 2860 Søborg +45 (0)56 64 50 00 +45 (0)56 64 50 55

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number: Poison Information Centre; emergency telephone, public + 45 82 12 12 (health

sector +45 35 31 55 55)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

English (GB) Denmark 1/14

: 10120DSC2396 Date of issue/Date of revision : 22 November 2019

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 2: Hazards identification

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

General : Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

Prevention : Not applicable. : Not applicable. Response **Storage** : Not applicable. **Disposal** : Not applicable.

P102, P101

Hazardous ingredients

Not applicable.

Supplemental label

: Safety data sheet available on request.

elements

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

: Not applicable.

articles

Special packaging requirements

Containers to be fitted

with child-resistant fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
(2-methoxymethylethoxy)propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≥1.0 - ≤5.0	Not classified.	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

English (GB)	Denmark	2/14
--------------	---------	------

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

English (GB) Denmark 3/14

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials: carbon oxides

metal oxide/oxides

5.3 Advice for firefighters

fighters

Special precautions for fire- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

English (GB) **Denmark** 4/14

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
(2-methoxymethylethoxy)propanol	Working Environment Authority (Denmark, 5/2018). Absorbed through skin. TWA: 309 mg/m³ 8 hours. TWA: 50 ppm 8 hours.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be

English (GB)	Denmark	5/14
--------------	---------	------

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 8: Exposure controls/personal protection

required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
propane-1,2-diol	DNEL	Long term Inhalation	10 mg/m³	General population	Local
	DNEL	Long term Inhalation	10 mg/m³	Workers	Local
	DNEL	Long term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	168 mg/m³	Workers	Systemic
(2-methoxymethylethoxy)propanol	DNEL	Long term Oral	0.33 mg/kg bw/ day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m³	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL DNEL	Long term Dermal Long term Inhalation	283 mg/kg bw/day 308 mg/m³	Workers Workers	Systemic Systemic

PNECs

INLOS				
Product/ingredient name	Type	Compartment Detail	Value	Method Detail
propane-1,2-diol	- - -	Fresh water Marine water Sewage Treatment Plant	260 mg/l 26 mg/l 20000 mg/l	Assessment Factors Assessment Factors Assessment Factors
(2-methoxymethylethoxy)propanol	- - - -	Fresh water sediment Marine water sediment Soil Fresh water Marine water	572 mg/kg dwt 57.2 mg/kg dwt 50 mg/kg dwt 19 mg/l 1.9 mg/l	Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning Assessment Factors Assessment Factors
	- - -	Sewage Treatment Plant Fresh water sediment Marine water sediment Soil	4168 mg/l 70.2 mg/kg 7.02 mg/kg 2.74 mg/kg	Assessment Factors Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

Hand protection

: Safety glasses with side shields. Use eye protection according to EN 166.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber, nitrile rubber

English (GB) Denmark 6/14

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 8: Exposure controls/personal protection

Personal protective equipment for the body should be selected based on the task **Body protection** being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respirator selection must be based on known or anticipated exposure levels, the Respiratory protection

> hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour

(Type A) and particulate filter P3

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Various **Odour** : Amine-like. **Odour threshold** Not available.

pН 7.5

Melting point/freezing point : May start to solidify at the following temperature: 0°C (32°F) This is based on

data for the following ingredient: water. Weighted average: -3.34°C (26°F)

Initial boiling point and boiling

range

: >37.78°C

: Closed cup: Not applicable. Flash point

: Highest known value: 0.02 ((2-methoxymethylethoxy)propanol) Weighted **Evaporation rate**

average: 0.01compared with butyl acetate

Flammability (solid, gas)

Upper/lower flammability or

explosive limits

Greatest known range: Lower: 1.1% Upper: 14% ((2-methoxymethylethoxy)

propanol)

: liquid

: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted Vapour pressure

average: 2.92 kPa (21.9 mm Hg) (at 20°C)

Highest known value: 5.1 (Air = 1) ((2-methoxymethylethoxy)propanol). Vapour density

Weighted average: 3.26 (Air = 1)

Relative density 1.26

Solubility(ies) : Partially soluble in the following materials: cold water.

Partition coefficient: n-octanol/

water

: Not applicable.

: Lowest known value: 207°C (404.6°F) ((2-methoxymethylethoxy)propanol). **Auto-ignition temperature Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

Viscosity : Kinematic (40°C): >0.21 cm²/s

: > 100 s (ISO 6mm) **Viscosity**

The product itself is not explosive, but the formation of an explosible mixture of **Explosive properties**

vapour or dust with air is possible.

English (GB) Denmark 7/14

Code : 10120DSC2396 Date of issue/Date of revision : 22 November 2019

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 9: Physical and chemical properties

Oxidising properties : Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propane-1,2-diol	LD50 Dermal LD50 Oral	Rabbit Rat	20800 mg/kg 20 g/kg	-
(2-methoxymethylethoxy)propanol	LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rabbit	500 ppm 9.5 g/kg 5.23 g/kg	4 hours - -

Conclusion/Summary: There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

English (GB) Denmark 8/14

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 11: Toxicological information

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely

routes of exposure

: Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No specific data.Ingestion: No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

English (GB) Denmark 9/14

Code : 10120DSC2396 Date of issue/Date of revision : 22 November 2019

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 11: Toxicological information

Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
(2-methoxymethylethoxy)propanol	Acute EC50 1919 mg/l	Daphnia	48 hours

Conclusion/Summary: There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary: There are no data available on the mixture itself.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propane-1,2-diol	-0.92	-	low

12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

English (GB)	Denmark	10/14
--------------	---------	-------

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be av

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction. **Hazardous waste**: Within the prese

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADDRID ADD HAD HAD				
	ADR/RID	ADN	IMDG	IATA	
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.	
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-	
14.3 Transport hazard class(es)	-	9	-	-	
14.4 Packing group	-	-	-	-	
14.5 Environmental hazards	No.	Yes.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.	

Additional information

ADR/RID : None identified.

ADN: The product is only regulated as a dangerous good when transported in tank vessels.

IMDG : None identified.IATA : None identified.

14.6 Special precautions for

user

: **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

English (GB) Denmark 11/14

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

14. Transport information

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

use of certain dangerous substances, mixtures and

articles

Ozone depleting substances (1005/2009/EU)

Not listed.

VOC for Ready-for-Use

Mixture

: IIA/d. Interior/exterior trim and cladding paints for wood and metal. EU limit values:

130g/l (2010.)

: Not applicable.

This product contains a maximum of 100 g/l VOC.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Denmark - Cancer risks

National Working Environment Authorities Ordinance on Measures to Prevent Cancer

Risks during Work with Substances and Preparations is applicable.

MAL-code : 1-1

Protection based on MAL

According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/ protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-1

Application: During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone. - Full mask with combined filter and arm protectors must be worn.

English (GB) Denmark 12/14

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 15: Regulatory information

During non-atomising spraying in existing* facilities of the combined-cabin, spraycabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied half mask, eye protection, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use

: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

: Not listed

Carcinogenic waste

: Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Not classified.		

Full text of abbreviated H statements

English (GB)	Denmark	13/14
--------------	---------	-------

Code : 10120DSC2396 Date of issue/Date of revision : 22 November 2019

DYRUP TRÆ & METAL EKSTRA STÆRK 90 HELBLANK

SECTION 16: Other information

Not applicable.

Full text of classifications [CLP/GHS]

Not applicable.

History

Date of issue/ Date of : 22 November 2019

revision

Date of previous issue : 6 November 2019

Prepared by : EHS Version : 1.04

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.